

IT42HD-4

Installation Guide

Each kit contains 4 x ITHD Brackets and fixings

- Split the IT42HD into two parts



- Line the Top Bracket of the IT42HD on the Fender in the correct mounting position for the Fender poles and mark the fender through the holes in the HD top bracket
- Using a 3/8 Drill bit, drill 8 holes through the Fender on the marked points.
- Take the plastic plate with bolts inserted and push through the underside of the fender.
- Place the Top part of the IT42HD over the bolt ends that have come through the Fender...
- Place a washer and Nut (As supplied) over each bolt and hand tighten.
- When all nuts and washers have been hand tightened. Tighten all nuts on bolts securely to a recommended 3.5 foot/pounds (4.75Nm).
- When all 8 bolts have been tightened close and clip the cover caps in place.



PLEASE NOTEALL BOLT COVERS ARE STRESSED TESTED BEFORE PACKING

TO AVOID OPERATIONAL DAMAGE

- PLEASE DO NOT TWIST THE BOLT COVER CAP, ONLY OPEN AND CLOSE VERTICALLY.
- PLEASE DO NOT TWIST THE COVER CAP TO OPEN...SIMPLY PUT A FLAT HEAD TOOL IN AND EASE OUT SLOWLY.
- THE COVER CAP SHOULD ONLY BE OPENED AND CLOSED WHEN FITTING OR REMOVING THE FENDER. THE COVER CAP IS THERE ONLY AS A VISUAL PRODUCT AND DOES NOT FORM ANY PART OF THE FENDER MOUNTING MECHANISM.